



REDWOOD, RV MASSIV

RUNDVIRKE SOLID SCANTLINGS IN ORIGINAL LENGTHS



Production:

Rundvirke solid scantlings are produced from selected pine cants of the finest Swedish origin. First, the cants are sawn, in original lengths parallel to the wane edge, into unedged stammware and then split-sawn into solid scantlings.

Our logs are not stored in water or sprinkled.

Drying:

A painstaking chamber-drying process employing a specially-designed program is used to maintain a moisture level of 14%±2%.

Our products are stored in a humidity-controlled storage hall prior to delivery.

Sorting:

In principle, the wane-edge side and 1 flat side are free of knots. The split side has a limited number of small and firm knots. The poorer flat side (underside) may also have single small firm knots. Surface knots that disappear in profilings/mouldings are not taken into account.

Scantlings with too many defects are downgraded to Grade B.

Generally free of cracks, no variations in colour and no insect damage.

A small number of either bent or deformed pieces may also be encountered.

Wane edge max. 20 mm, measured across the edge. Quality grading is determined by the condition of the end product, i.e., the profiled solid scantlings; see drawing.

Measuring: 10:10 cm

Dimensions: (standard)

50x90/100/125 mm

63x75/80/90/100/125/150 mm

75x90/100/120/130/150 mm

Customized dimensions available upon request.

Assorted Lengths:

1,8-3,3 m

3,4-4,2 m

4,3-5,7 m

Falling lengths.

Marking: Blue-coloured RV logo.

