



REDWOOD, RV STAMMWARE

QUALITY FIRST-CLASS NORTHERN SWEDISH UNEDGED STAMMWARE



Production:

Rundvirke stammware is produced by using carefully selected cants of the finest Swedish origin.

Our logs are not stored in water or sprinkled.

Drying:

A painstaking chamber-drying process employing a specially-designed program is used to maintain a moisture level of 14%+2%.

Sorting and cross-cutting:

Screening and sorting according to the quality grades for sawing and drying Grade A products, including approximately 15% inferior-grade products.

Black-coloured chalk markings are used on items which do not meet length and width specifications and also on inferior-grade products marked Urlägg (=✓). Excess and inferior-grade products are never delivered to customers.

Measuring:

Length 30:30 cm, width 1:1 cm measured at the midpoint of the narrow face of the board rounded off downwards. Package specifications provided in Swedish and German standard measure.

Dimensions: (Standard)

Narrow size: 75 mm

Normal sizes: 40/44/50/63/75 mm

Extra-wide sizes: 50/63/75 mm

Lengths:

Falling lengths.

Approximate average length 4,1-4,3 m.

Average Widths:

Narrow 20-22 cm

Normal 25-28 cm

Extra-wide 30 cm +

Marking:

Blue-coloured RV logo as well as the length and the width of each board printed in compliance with German standards, i.e., the width in cm measured on the half-wane at the midpoint of each board as well as the length in dm, 1:1 dm.