



WHITEWOOD, RV MASSIV

RUNDVIRKE SOLID SCANTLINGS IN ORIGINAL LENGTHS



Production:

Rundvirke solid scantlings are produced from selected spruce cants of the finest Swedish origin. First, the cants are sawn, in original lengths parallel to the waney edge, into unedged stammware and then split-sawn into solid scantlings. The annual growth rings should be half-standing/standing.

Our logs are not stored in water or sprinkled.

Drying:

A painstaking chamber-drying process employing a specially-designed program is used to maintain a moisture level of 14%+/-2%.

Our products are stored in a humidity-controlled storage hall prior to delivery.

Sorting:

In principle, the wane-edge side and 1-2 flat sides are free of knots. A limited number of firm knots are allowed on the sawn side. On both flat sides and on the waned side, small (7-8 mm) a restricted number of knots are permitted. Surface knots that disappear in profilings/mouldings are not taken into account. Scantlings having too many defects are downgraded to Grade B.

Generally free of cracks, single small-size resin pockets may be found; no variations in colour and no insect damage.

A small number of either bent or deformed pieces may also be encountered.

Wane edge max. 20 mm, measured across the edge.

Quality grading is determined by the condition of the end product, i.e., the profiled solid scantlings; see drawing.

Measuring: 10:10 cm

Dimensions: (standard)

50x90/100 mm

63x90/100 mm

75x90/100 mm

Customized dimensions available upon request.

Assorted Lengths:

1,8-3,3 m

3,4-4,2 m

4,3-5,7 m

Marking: Blue-coloured RV logo.

